

Color Blox 2.0

12x24 Porcelain

mosaic 
Products. Design. Solutions.



03CBX311224



03CBX031224



03CBX331224



03CBX081224



03CBX011224




03CBX071224



03CBX371224



03CBX141224



03CBX341224



03CBX351224



03CBX361224



03CBX131224



03CBX381224



03CBX171224



03CBX321224



3x3 Mosaic



Tile: 4x12 - 6x6 - 12x12 - 12x24 - 24x24

Mosaic: 3x3

Trim: 3x3 Bullnose - 3x3 Corner
3x3 Cove Base - 4x24 Bullnose
4x12 Corner - 6x12 Cove Base
6x8 Cove Base Corner

Not all colors available in all sizes or finishes

For more information
and images:



Color Blox 2.0

Porcelain



Technical Characteristics

Test Item	Test Method	Test Result
Breaking Strength	ASTM C648	500 lbf
Bond Strength	ASTM C482	> 200 psi
Chemical Resistance	ASTM C650	Unaffected
Frost Resistance	ASTM C1026	Resistant
Water Absorption	ASTM C373	< 0.20%
Scratch Hardness	Mohs Scale	7
DCOF	AcuTest	0.50-0.60

Nominal Size	Actual Size	Thickness	Finish	Rectified
4" x 12" *	3-3/4" x 11-3/4"	9.5 mm	Unpolished	-
6" x 6"	5-13/16" x 5-13/16"	9.5 mm	Unpolished	-
12" x 12"	11-13/16" x 11-13/16"	9.5 mm	Unpolished	-
12" x 24"	11-13/16" x 23-13/16"	9.5 mm	Unpolished	-
24" x 24"	23-13/16" x 23-13/16"	10.5 mm	Unpolished	-
3" x 3" Mosaic	11-3/4" x 11-3/4"	6.4 mm	Unpolished	-
4" x 24" Bullnose	3-3/4" x 23-13/16"	9.5 mm	Unpolished	-
4" x 12" Bullnose Corner	3-3/4" x 11-3/4"	9.5 mm	Unpolished	-
3" x 3" Bullnose Mounted	2-7/8" x 11-3/4"	6.4 mm	Unpolished	-
3" x 3" Bullnose Corner	2-7/8" x 2-7/8"	6.4 mm	Unpolished	-
3" x 3" Cove Base Mounted	3-5/8" x 11-3/4"	6.4 mm	Unpolished	-
6" x 12" Cove Base	5-7/8" x 11-3/4"	9.5 mm	Unpolished	-
6" x 8" Cove Base Corner	5-7/8" x 7-3/4"	9.5 mm	Unpolished	-

* 4x12 is custom cut – Inquire with a sales representative for lead time.

Installation Note: The TCNA recommends rectangular shape tile be installed with maximum of 33% offset in order to resolve any possible lippage from one tile to the next.