



Technical Characteristics

Test Item	Test Method	Test Result
Breaking Strength	ASTM C648	≥ 450 lbf
Bond Strength	ASTM C482	> 200 psi
Chemical Resistance	ASTM C650	Unaffected
Frost Resistance	ASTM C1026	Resistant
Water Absorption	ASTM C373	< 0.50%
Scratch Hardness	Mohs Scale	7
DCOF	AcuTest	0.50-0.60

Nominal Size	Actual Size	Thickness	Finish	Rectified
12" x 24"	11.69" x 23.5"	9.5 mm	Unpolished	Yes
24" x 24"	23.5" x 23.5"	9.5 mm	Unpolished	Yes
24" x 48"	23.5" x 47.13"	10.5 mm	Unpolished	Yes
2" x 2" Mosaic	11.73" x 11.73"	9.5 mm	Unpolished	-
10" x 11" Mixed Hex Mosaic	10.2" x 10.63"	9.5 mm	Unpolished	-
2" x 12" Metallic Deco	1.85" x 11.69"	9.5 mm	Satin	-
4" x 24" Bullnose	3.78" x 23.5"	9.5 mm	Unpolished	-
6" x 12" Cove Base	5.91" x 11.69"	9.5 mm	Unpolished	-

Installation Note: The TCNA recommends rectangular shape tile be installed with maximum of 33% offset in order to resolve any possible lippage from one tile to the next.



12x24 Porcelain



03NVM011224



03NVM021224



03NVM031224



03NVM041224




03NVM051224



03NVM061224

Mosaics + Decos



2x2 Mosaic
Available in all colors



NVM01 Hex with Gold



NVM01 Hex with Iron



NVM02 Hex with Iron



NVM03 Hex with Iron



NVM04 Hex with Gold
Available with Iron



NVM05 Hex with Iron



NVM06 Hex with Iron



White Iron Molten Deco



White Iron Perforated Deco



Champagne Gold Molten Deco



Champagne Gold Perforated Deco



Rubbed Bronze Molten Deco



Rubbed Bronze Perforated Deco

Tile: 12x24 - 24x24 - 24x48
 Mosaics: 2x2 - 10x11 Mixed Hex
 Deco: 2x12 Metallic
 Trim: 4x24 Bullnose - 6x12 Cove Base

Not all colors available in all sizes or finishes

