

# Owen Stone

12x24 Porcelain



03OST011224



03OST031224



03OST051224



2x2 Mosaic



Triangle Mosaic



03OST021224



03OST041224



03OST061224



Tile: 12x24 - 24x24 - 24x48

Mosaics: 2x2 - Triangle

Trim: 4x24 Bullnose - 6x12 Cove Base

Outdoor: 12x24 - 24x24

For more information  
and images:





## Technical Characteristics

Test Item	Test Method	Test Result
Breaking Strength	ASTM C648	> 450 lbf
Bond Strength	ASTM C482	> 200 psi
Chemical Resistance	ASTM C650	Unaffected
Frost Resistance	ASTM C1026	Resistant
Water Absorption	ASTM C373	< 0.20%
Scratch Hardness	Mohs Scale	7
DCOF	AcuTest	0.50-0.60 (Unpolished); 0.42-0.52 (Leathered); 0.60-0.70 (Exterior/Textured)

Nominal Size	Actual Size	Thickness	Finish	Rectified
12" x 24"	11.69" x 23.5"	9.5 mm	Unpolished, Leathered or Exterior	Yes
24" x 24"	23.5" x 23.5"	9.5 mm	Unpolished, Leathered or Exterior	Yes
24" x 48"	23.5" x 47.13"	10.5 mm	Unpolished or Leathered	Yes
2" x 2" Mosaic	11.73" x 11.73"	9.5 mm	Unpolished or Leathered	-
Triangle Mosaic *	8.54" x 14.65"	9.5 mm	Leathered	-
4" x 24" Bullnose	3.78" x 23.5"	9.5 mm	Unpolished or Leathered	-
6" x 12" Cove Base	5.91" x 11.69"	9.5 mm	Unpolished	-

\* Due to this mosaic's design, caution should be used when installing on surfaces that might contact bare skin or other delicate materials. To prevent possible injury or damage from sharp corners that might be exposed above the grout line, install per ANSI 108 guidelines in order to minimize or prevent lippage.

Installation Note: The TCNA recommends rectangular shape tile be installed with maximum of 33% offset in order to resolve any possible lippage from one tile to the next.