

Sand Garden

12x24 Porcelain




03SDG011224SPO (semi)
03SDG011224 (unpol)



03SDG021224SPO (semi)
03SDG021224 (unpol)



3x3 Mosaic



Trapezoid



03SDG031224SPO (semi)
03SDG031224 (unpol)



03SDG041224SPO (semi)
03SDG041224 (unpol)



Tile: 12x24 - 24x24
Mosaics: 3x3 - 11x14 Trapezoid
Trim: 4x24 Bullnose - 6x12 Cove Base

For more information
and images:





Technical Characteristics

Test Item	Test Method	Test Result
Breaking Strength	ASTM C648	≥ 450 lbf
Bond Strength	ASTM C482	> 200 psi
Frost Resistance	ASTM C1026	Resistant
Chemical Resistance	ASTM C650	Unaffected
Stain Resistance	ASTM C1378	Unaffected
Crazing Resistance	ASTM C424	Resistant
Thermal Shock Resistance	ASTM C424	Resistant
Water Absorption	ASTM C484	< 0.5%
Scratch Hardness	Mohs Scale	7
DCOF	AcuTest	0.42-0.52 (Semi-Polished); 0.50-0.60 (Unpolished)

Nominal Size	Actual Size	Thickness	Finish	Rectified
12" x 24"	11.69" x 23.50"	9.5 mm	Semi-polished or Unpolished	Yes
24" x 24"	23.50" x 23.50"	9.5 mm	Semi-polished or Unpolished	Yes
3" x 3" Mosaic	11.69" x 11.69"	9.5 mm	Unpolished	-
11" x 14" Trapezoid	11.25" x 13.97"	9.5 mm	Unpolished	-
4" x 24" Bullnose	3.81" x 23.50"	9.5 mm	Semi-polished or Unpolished	-
6" x 12" Cove Base	5.90" x 11.69"	9.5 mm	Unpolished	-

Installation Note: The TCNA recommends rectangular shape tile be installed with maximum of 33% offset in order to resolve any possible lippage from one tile to the next.