

# Stone Fiction

12x24 Porcelain

mosaic   
Products. Design. Solutions.



03STF011224



03STF031224



2x2 Mosaic



03STF021224



03STF041224



Tile: 12x24 - 24x24  
Mosaic: 2x2  
Trim: 4x24 Bullnose - 6x12 Cove Base  
Outdoor: 24x24

For more information  
and images:



## Technical Characteristics

Test Item	Test Method	Test Result
Breaking Strength	ASTM C648	> 450 lbf
Bond Strength	ASTM C482	> 200 psi
Chemical Resistance	ASTM C650	<b>Unaffected</b>
Frost Resistance	ASTM C1026	<b>Resistant</b>
Water Absorption	ASTM C373	< 0.50%
Scratch Hardness	Mohs Scale	7
DCOF	AcuTest	<b>0.42-0.52 (Unpolished); 0.60-0.70 (Exterior)</b>

Nominal Size	Actual Size	Thickness	Finish	Rectified
12" x 24"	11-13/16" x 23-13/16"	9.5 mm	Unpolished	-
24" x 24"	23-13/16" x 23-13/16"	9.5 mm	Unpolished or Exterior	-
2" x 2" Mosaic	11-15/16" x 11-15/16"	9.5 mm	Unpolished	-
4" x 24" Bullnose	3-13/16" x 23-13/16"	9.5 mm	Unpolished	-
6" x 12" Cove Base	5-7/8" x 11-3/4"	9.5 mm	Unpolished	-

Installation Note: The TCNA recommends rectangular shape tile be installed with maximum of 33% offset in order to resolve any possible lippage from one tile to the next.

