

Luxury

12x12 Porcelain


mosaic 
Products. Design. Solutions.



04LUXCAL12 (matte)
04LUXCAL12P (polished)



04LUXNER12 (matte)
04LUXNER12P (polished)



Hexagon Mosaic
(matte or polished)



04LUXABR12 (matte)
04LUXABR12P (polished)



04LUXAGR12 (matte)
04LUXAGR12P (polished)



Tile: 3x12 - 12x12 - 12x24 - 24x24 - 24x48

Mosaics: 3" Hexagon

Trim: 3x12 Bullnose

Not all sizes available in all finishes

For more information
and images:





Technical Characteristics

Specs	Test Method	Industry Standard	Test Result	
Water Absorption	ASTM C373	≤ 0.5%	≤ 0.5%	
Surface Wear Resistance	ANSI A137.1	Surface wear resistance properties of glazed vitreous and porcelain tile.	All Commercial / Residential	
Chemical Resistance	ASTM C650	No tile sample shows visible defects after continuous contact with a variety of chemicals for 24 hours.	Not Affected	
DCOF (Wet)	ANSI A326.3	≥ 0.42	≥ 0.42	
Stain Resistance	ASTM C1378	Surfaces are exposed to staining agents for 24 hours followed by four cleaning procedures.	Not Affected	
Breaking Strength	ASTM C648	≥ 275 lbf	≥ 300 lbf	
Freeze Resistance	ASTM C1026	No tile sample shows visible defects after repeated processes of freezing and thawing.	Resistant	
Warpage Edge	ASTM C485	± 0.40% or ± 0.05 in (± 1.8 mm)	± 0.40%	Rectified
			± 0.50%	Calibrated
Warpage Diagonal	ASTM C485	± 0.40% or ± 0.07 in (± 1.8 mm)	± 0.40%	Rectified
			± 0.50%	Calibrated
Wedging	ASTM C502	± 0.25% or ± 0.03 in (± 0.8 mm)	± 0.25%	Rectified
			± 0.50%	Calibrated
Thickness	ASTM C499	Range: ± 0.04 in	≤ 0.04 in	
Recycled Content	As reported		≥ 40% Pre-Consumer	

Nominal Size	Actual Size	Thickness	Finish	Rectified
3" x 12"	2.95" x 11.81"	8 mm	Polished	Yes
12" x 12"	11.81" x 11.81"	8 mm	Matte or Polished	Yes
12" x 24"	11.81" x 23.62"	8 mm	Matte or Polished	Yes
24" x 24"	23.62" x 23.62"	8 mm	Matte or Polished	Yes
24" x 48"	23.62" x 47.24"	8 mm	Matte or Polished	Yes
3" Hexagon Mosaic	9.06" x 11.02"	8 mm	Matte or Polished	-
3" x 12" Bullnose	2.95" x 11.81"	8 mm	Matte or Polished	-

All tiles have an allowance for variations in size. All of our tiles are produced with ASTM and ANSI standards. When working with a product that is baked in a kiln, variation in size is a natural part of the process.

Installation Note: The TCNA recommends rectangular shape tile be installed with maximum of 33% offset in order to resolve any possible lippage from one tile to the next.