

+ One

12x24 Color Body Porcelain



2x2 Mosaic

04ONECHA1224 (matte) 04ONEGRE1224 (matte) 04ONEMUD1224 (matte)
04ONECHA1224P (polished) 04ONEGRE1224P (polished) 04ONEMUD1224P (polished)



04ONEASH1224 (matte) 04ONEPLU1224 (matte) 04ONECOA1224 (matte)
04ONEASH1224P (polished) 04ONEPLU1224P (polished) 04ONECOA1224P (polished)



Tile: 12x24 - 24x24 - 24x48 - 48x48
Mosaic: 2x2
Trim: 3x24 Bullnose - 6x12 Cove Base
Outdoor: 20mm 12x48 - 24x24 - 24x48
Not all colors available in all sizes or finishes

For more information
and images:



+ One

Color Body Porcelain



Technical Characteristics

Specs	Test Method	Industry Standard	Test Result	
Water Absorption	ASTM C373	≤ 0.5%	≤ 0.4%	
Surface Wear Resistance	ANSI A137.1	Surface wear resistance properties of glazed vitreous and porcelain tile.	All Commercial / Residential	
Chemical Resistance	ASTM C650	No tile sample shows visible defects after continuous contact with a variety of chemicals for 24 hours.	Not Affected	
DCOF (Wet)	ANSI A326.3	≥ 0.42	≥ 0.42 (Matte)	
Stain Resistance	ASTM C1378	Surfaces are exposed to staining agents for 24 hours followed by four cleaning procedures.	Not Affected	
Breaking Strength	ASTM C648	≥ 250 lbf	≥ 300 lbf (8 mm); ≥ 400 lbf (10 mm)	
Freeze Resistance	ASTM C1026	No tile sample shows visible defects after repeated processes of freezing and thawing.	Resistant	
Warpage Edge	ASTM C485	± 0.40% or ± 0.05 in (± 1.8 mm)	± 0.40%	Rectified
			± 0.50%	Calibrated
Warpage Diagonal	ASTM C485	± 0.40% or ± 0.07 in (± 1.8 mm)	± 0.40%	Rectified
			± 0.50%	Calibrated
Wedging	ASTM C502	± 0.25% or ± 0.03 in (± 0.8 mm)	± 0.25%	Rectified
			± 0.50%	Calibrated
Thickness	ASTM C499	Range: ± 0.04 in	≤ 0.04 in	
Recycled Content		As reported	≥ 20% Pre-Consumer	

Nominal Size	Actual Size	Thickness	Finish	Rectified
12" x 24"	11.73" x 23.6"	8 mm	Matte or Polished	Yes
24" x 24"	23.6" x 23.6"	8 mm	Matte or Polished	Yes
24" x 48"	23.6" x 47.3"	8 mm	Matte or Polished	Yes
48" x 48"	47.3" x 47.3"	8 mm	Matte	Yes
2" x 2" Mosaic	12" x 12"	8 mm	Matte or Polished	-
3" x 24" Bullnose	2.85" x 23.6"	8 mm	Matte or Polished	-
6" x 12" Cove Base *	6.5" x 11.8"	7 mm	Matte	-
12" x 48" Paver	11.6" x 47"	20 mm	Grip	Yes
24" x 24" Paver	23.5" x 23.5"	20 mm	Grip	Yes
24" x 48" Paver	23.5" x 47"	20 mm	Grip	Yes

* This item is made to order. Please check with a sales representative for current lead times.

All tiles have an allowance for variations in size. All of our tiles are produced with ASTM and ANSI standards. When working with a product that is baked in a kiln, variation in size is a natural part of the process.

Installation Note: The TCNA recommends rectangular shape tile be installed with maximum of 33% offset in order to resolve any possible lippage from one tile to the next.