Beyond Dolomite

12x24 Porcelain















Stripes (available in all colors)





Tile: 12x24 - 24x48
Wall Tile: 12x24 Stripes
Mosaics: 2x2 - Apex

Trim: 3x24 Bullnose - 6x12 Cove Base

Outdoor: 20mm 24x24 (WAR only)

12x24 available in matte finish only; Matte and Polished finishes available in 24x48 24x48 Polished is made in Italy

For more information and images:

Beyond Dolomite

Porcelain











Technical Characteristics

		Porcelain Tile Specification				
Characteristic	Test Method	Calibrated	Rectified	Value		
Nominal Size		+ 3%	- 3% or + 2%	Compliant		
Caliber Range	ASTM C499	± 0.5% or ± 0.08 in	± 0.25% or ± 0.03 in	Compliant		
Thickness		Range: 0.04 in		Compliant		
Wedging	ASTM C502	± 0.5% or ± 0.08 in	$\pm 0.25\%$ or ± 0.03 in	Compliant		
Warpage Edge	A OTA 4 O 4 O 5	± 0.75% or ± 0.09 in	± 0.40%	Compliant		
Warpage Diagonal	ASTM C485	± 0.5% or ± 0.08 in	± 0.40% or ± 0.07 in	Compliant		
Water Absorption	ASTM C373	≤ 0.5%		≤ 0.5%		
		Matte / Polished	Outdoor 20mm	Matte	e / Pol.	Outdoor 20mm
Breaking Strength	ASTM C648	Average ≥ 250 lbf Individual ≥ 225 lbf	≥ 2000 lbf avg	≥ 350	lbf avg	≥ 2200 lbf avg
		Outdoor 20mm		Outdoor 20mm		
Modulus of Rupture	ASTM C1050	5000) psi.	Compliant		
Bond Strength	ASTM C482	≥ 50) psi	≥ 100 psi		
Resistance to Freeze/ Thaw Cycling	ASTM C1026	As Reported		Resistant		
Thermal Shock Resistance	ASTM C484	As Reported		Resistant		
Chemical Resistance	ASTM C650	As Reported		Unaffected		
Stain Resistance	ASTM C1378	As Reported		Unaffected		
				Matte	Pol.	Outdoor 20mm
Dynamic Coefficient of Friction (DCOF)	ANSI A326.3	As Reported		≥ 0.42 Wet	≥ 0.42 Dry	≥ 0.60 Wet

Nominal Size	Actual Size	Thickness	Finish	Rectified
12" x 24"	11.75" x 23.62"	9 mm	Matte	Yes
12" x 24" Stripes Wall	11.75" x 23.62"	9 mm	Matte	Yes
24" x 24" Paver	23.62" x 23.62"	20 mm	Matte	Yes
24" x 48"	23.62" x 47.25"	9 mm	Matte or Polished	Yes
2" x 2" Mosaic	11.75" x 11.75"	9 mm	Matte	-
Apex Mosaic	11" x 11"	9 mm	Matte	-
3" x 24" Bullnose	2.83" x 23.62"	9 mm	Matte or Polished	-
6" x 12" Cove Base	5.91" x 11.81"	8.5 mm	Matte	-

All tile is subject to variations in technical specifications and performance due to the inherent variables in the raw materials and production process. It is understood that test results on a particular product may vary slightly from tile to tile and from test to test. Test results are not guarantees of minimum or maximum thresholds of performance.

