

Memory Oak

8x40 Porcelain



15MEMWHI840




15MEMASH840



15MEMVAN840



15MEMCAR840



15MEMBRO840



15MEMMOK840



Spa
Available in all colors



Chevron
Available in all colors



Tile: 8x40, 8x40 Chevron, 8x40 Spa
Mosaic: N/A
Trim: N/A

For more information
and images:





Technical Characteristics

Characteristic	Test Method	Porcelain Tile Specification		Value
		Calibrated	Rectified	
Nominal Size	ASTM C499	+ 3%	- 3% or + 2%	Compliant
Caliber Range		- 0.5% or - 0.08 in	- 0.25% or - 0.03 in	Compliant
Thickness		Range: 0.4 in		Compliant
Wedging	ASTM C502	- 0.5% or - 0.08 in	- 0.25% or - 0.03 in	Compliant
Warpage Edge	ASTM C485	- 0.75% or - 0.09 in	- 0.40%	Compliant
Warpage Diagonal		- 0.5% or - 0.08 in	- 0.40% or - 0.07 in	Compliant
Water Absorption	ASTM C373	≤ 0.5%		≤ 0.5%
Breaking Strength	ASTM C648	Average ≥ 250 lbf; Individual ≥ 225 lbf		≥ 350 lbf avg
Bond Strength	ASTM C482	≥ 50 psi		≥ 100 psi
Resistance to Freeze/Thaw Cycling	ASTM C1026	As Reported		Resistant
Thermal Shock Resistance	ASTM C484	As Reported		Resistant
Chemical Resistance	ASTM C650	As Reported		Unaffected
Stain Resistance	ASTM C1378	As Reported		Unaffected
Dynamic Coefficient of Friction (DCOF)	ANSI A326.3	As Reported		≥ 0.42 Wet

Nominal Size	Actual Size	Thickness	Finish	Rectified
8" x 40"	7.75" x 39.37"	9 mm	Matte	Yes
8" x 40" Chevron	7.75" x 39.37"	9 mm	Matte	Yes
8" x 40" Spa	7.75" x 39.37"	9 mm	Matte	Yes

All tile is subject to variations in technical specifications and performance due to the inherent variables in the raw materials and production process. It is understood that test results on a particular product may vary slightly from tile to tile and from test to test. Test results are not guarantees of minimum or maximum thresholds of performance.

Installation Note: Due to its linear plank shape, this material requires particular care when it comes to installation. The tile will look its best when offset is less than 33%. The staggered installation will minimize lippage which is common in tiles of this format. No claim will be honored after installation.