Endless 12x24 Glazed Porcelain





70ENDWHI1224



70ENDBEI1224



70ENDWAR1224



70ENDSTO1224



2x2 Mosaic



Tile:12x24Mosaic:2x2Trim:3x12 Bullnose

For more information and images:



v.3-24

Endless Glazed Porcelain



Technical Characteristics

Reference		Characteristic	Test Method	Required Values		Value
Dimensional Standard	Calibrated	Nominal Size	ASTM C499	± 3%		Comply
		Caliber Range	ASTM C499	± 0.5%	± 0.08 in	Comply
		Warpage Edge	ASTM C485	± 0.5%	± 0.07 in	Comply
		Warpage Diagonal	ASTM C485	± 0.5%	± 0.07 in	Comply
		Wedging	ASTM C502	± 0.5%	± 0.08 in	Comply
	Rectified	Nominal Size	ASTM C499	- 3%	+ 2%	Comply
		Caliber Range	ASTM C499	± 0.25%	± 0.03 in	Comply
		Warpage Edge	ASTM C485	±0.4%	± 0.05 in	Comply
		Warpage Diagonal	ASTM C485	±0.4%	± 0.07 in	Comply
		Wedging	ASTM C502	± 0.25%	± 0.03 in	Comply
		Thickness	ASTM C499	± 0.040 in		Comply
		DEEP Abrasion	ASTM C1243	< 175mm ³		~ 40 mm ³
		Bond Strength	ASTM C482	≥ 50) psi	Comply
		Water Absorption	ASTM C373	Maximu	m 0.5%	~ 0.2%
Ţ	2	Thermal Shock Resistance	ASTM C484	Pa	ISS	Comply
	al lua	Chemical Resistance	ASTM C650	Pa	ISS	Comply
		Stain Resistance	ASTM C1378	Pa	ISS	Comply
Mechanical Standard		Breaking Strength	ASTM C648	\geq 275 lbf		Comply
		Resistance to Freeze / Thaw Cycling	ASTM C1026	As Reported		Comply
ž		Scratch Hardness	Mohs	Declared Value		Mohs ≥ 6
		Fire reaction - floor	EN 13823	Not Required		A1fl class (No reaction)
		Fire reaction - wall	EN 13823	Not Required		A1fl class (No reaction)
		VOC	No VOC			
		Dynamic Coefficient of Friction DCOF	ANSI A326.3	3 ≥ 0.42 Wet		0.66

Nominal Size	Actual Size	Thickness	Rectified
12" x 24"	11.81" x 23.62"	8.5 mm	-
2" x 2" Mosaic	11.81" x 11.81"	8.5 mm	-
3" x 12" Bullnose	3.15" x 11.81"	8.5 mm	-

Values reflect an average among tests performed in the manufacturer's laboratory according to the standard requirements and/or through a third party laboratory. Tests are performed on actual production, first choice material. Values may vary between single individual production runs.

Installation Note: The TCNA recommends rectangular shape tile be installed with maximum of 33% offset in order to resolve any possible lippage from one tile to the next.

