

Braewood

6x36 Porcelain



75BRAWHI636N



75BRADUS636N



75BRASAD636N



75BRAMID636



Commercial Projects Only

Tile: 6x36

For more information
and images:



Technical Characteristics

| Test Item | Test Method | Test Result |
|--------------------------|--------------|------------------|
| Breaking Strength | ASTM C648 | ≥ 325 lbs. |
| Scratch Hardness | MOH'S | 7 |
| Chemical Resistance | ASTM C650-04 | Class A |
| Abrasion Resistance | ASTM C1027 | Class IV |
| Thermal Shock Resistance | ASTM C484 | Resistant |
| Frost Resistance | ASTM C1026 | Resistant |
| Water Absorption | ASTM C373 | < 0.5% |
| DCOF (Wet) | ASTM C1028 | ≥ 0.42 |
| Category of Use | ANSI A326.3 | IW |

| Nominal Size | Actual Size | Thickness | Finish | Rectified |
|--------------|--------------------|-----------|--------|-----------|
| 6" x 36" | 5-5/16" x 35-9/16" | 8.2 mm | Matte | - |

All tile is subject to variations in technical specifications and performance due to the inherent variables in the raw materials and production process. It is understood that test results on a particular product may vary slightly from tile to tile and from test to test. Test results are not guarantees of minimum or maximum thresholds of performance.

Installation Note: Due to its linear plank shape, this material requires particular care when it comes to installation. The tile will look its best when offset is less than 33%. The staggered installation will minimize lippage which is common in tiles of this format. No claim will be honored after installation.

