

Bryce Wood

6x36 Porcelain



75BRYWHI636N



75BRYBEI636N



75BRYGRA636N



75BRYBRO636N



QuickSHIP

Tile: 6x36

Mosaics: N/A

Trim: N/A

For more information
and images:



Technical Characteristics

Test Item	Test Method	Test Result
Breaking Strength	ASTM C648	≥ 325 lbs.
Scratch Hardness	MOH'S	7
Chemical Resistance	ASTM C650-04	Class A
Abrasion Resistance	ASTM C1027	Class III
Thermal Shock Resistance	ASTM C484	Resistant
Frost Resistance	ASTM C1026	Resistant
Water Absorption	ASTM C373	< 0.5%
DCOF (Wet)	ASTM C1028	≥ 0.42
Category of Use	ANSI A326.3	IW

Nominal Size	Actual Size	Thickness	Finish	Rectified
6" x 36"	5-5/16" x 35-9/16"	8.2 mm	Matte	-

All tile is subject to variations in technical specifications and performance due to the inherent variables in the raw materials and production process. It is understood that test results on a particular product may vary slightly from tile to tile and from test to test. Test results are not guarantees of minimum or maximum thresholds of performance.

Installation Note: Due to its linear plank shape, this material requires particular care when it comes to installation. The tile will look its best when offset is less than 33%. The staggered installation will minimize lippage which is common in tiles of this format. No claim will be honored after installation.



For your convenience, select products are stocked in our Central Service Center.