

Lassen Wood

6x36 Porcelain



75LASOYS636



75LASTAU636



75LASFAW636



75LASCOF636



Commercial Projects Only

Tile: 6x36

For more information
and images:





Technical Characteristics

Test Item	Test Method	Test Result
Breaking Strength	ASTM C648	≥ 325 lbs.
Scratch Hardness	MOH'S	7
Chemical Resistance	ASTM C650-04	Class A
Abrasion Resistance	ASTM C1027	Class III
Thermal Shock Resistance	ASTM C484	Resistant
Frost Resistance	ASTM C1026	Resistant
Water Absorption	ASTM C373	< 0.5%
DCOF (Wet)	ASTM C1028	≥ 0.42
Category of Use	ANSI A326.3	IW

Nominal Size	Actual Size	Thickness	Finish	Rectified
6" x 36"	5-15/16" x 35-9/16"	8.2 mm	Matte	-

All tile is subject to variations in technical specifications and performance due to the inherent variables in the raw materials and production process. It is understood that test results on a particular product may vary slightly from tile to tile and from test to test. Test results are not guarantees of minimum or maximum thresholds of performance.

Installation Note: Due to its linear plank shape, this material requires particular care when it comes to installation. The tile will look its best when offset is less than 33%. The staggered installation will minimize lippage which is common in tiles of this format. No claim will be honored after installation.

