

Pro

12x24 Glazed & Polished Porcelain



88PROIVO1224 (Matte)
88PROIVO1224P (Polished)



88PRONUD1224 (Matte)
88PRONUD1224P (Polished)



Tile: 12x24
Mosaic: N/A
Trim: N/A

For more information
and images:



Technical Characteristics

| Specs | Test Method | Required Values | Test Result - Polished | Test Result - Matte |
|--|-------------|-----------------|------------------------|---------------------|
| Water Absorption | ASTM C373 | ≤0.5% | ≤0.5% | ≤0.5% |
| Breaking Strength | ASTM C648 | ≥350 | ≥350 | ≥350 |
| Scratch Hardness | MOHs Scale | - | 3 | 5 |
| Chemical Resistance | ASTM C650 | Unaffected | Unaffected | Unaffected |
| Frost Resistance | ASTM C1026 | Resistant | Resistant | Resistant |
| PEI - Glazed Tiles | ASTM C1027 | | III | IV |
| Minimum Bond Strength (PSI) | ASTM C482 | ≥50 psi | 165 | 165 |
| Dynamic Coefficient of Friction (DCOF) | ASTM A137.1 | ≥0.42 | <0.40 | ≥0.42 |
| Shade and Texture Rating | CTDA "V" | - | V3 | V3 |
| Facial Dimensions | ASTM C499 | 1.5% Max | Pass | Pass |
| Range of Thickness | ASTM C499 | 0.040 Max | Pass | Pass |
| Warpage | ASTM C485 | 0.75% | Pass | Pass |
| Wedging | ASTM C502 | 1.0% Max | Pass | Pass |

| Nominal Size | Actual Size | Thickness | Finish | Rectified |
|--------------|-----------------|-----------|-------------------|-----------|
| 12" x 24" | 11.81" x 23.62" | 8.5 mm | Matte or Polished | Yes |

All tile is subject to variations in technical specifications and performance due to the inherent variables in the raw materials and production process. It is understood that test results on a particular product may vary slightly from tile to tile and from test to test. Test results are not guarantees of minimum or maximum thresholds of performance.